

IN THE CLAIMS:

Kindly cancel claims 1-9, 13 and 20, and amend claims 10-12 as follows:

1-9. (Cancelled)

10. (Currently Amended) An injection molding method, said method comprising:

moving wherein an injection portion moving along a line of a plurality of resin supplying ports in communication with a cavity, while injecting molten resin from the injection portion into the resin supplying ports, so as to for supplying a supply the molten resin to [[a]] the cavity,

wherein injects the molten resin is sequentially injected into [[from]] the resin supplying [[port]] ports at a low injection pressure by moving the injection portion from one resin supplying port and thereafter moves to the next resin supplying port so as to inject, thereby injecting molten resin to all the resin supplying ports in a sequential manner.

11. (Currently Amended) The [[An]] injection molding method as claimed in claim 10,

wherein, during injection of the molten resin into the cavity, said injection portion moves from a to the upper resin supplying [[ports]] port disposed at a low elevation end of the line of a plurality of resin supplying ports to a from the lower end resin supplying port disposed at an upper elevation end of the [[in a]] plurality of resin supplying ports, which are arranged in a vertical direction, and injects the molten resin into said cavity.

12. (Currently Amended) The ~~[[An]]~~ injection molding method as claimed in claim 10, wherein the injection of said molten resin from said injection portion to one resin supplying port is ~~finished~~ terminated by a detection sensor in communication with the injection portion and disposed ~~provided~~ in a predetermined position of said cavity for detecting a charging amount of the molten resin, and

wherein, upon termination of injection of the molten resin at the one resin supplying port, said injection portion moves to the ~~[[other]]~~ next resin supplying ~~[[ports]]~~ port in the line of plurality of resin supplying ports.

13. (Cancelled)

14. (Withdrawn) An injection molding apparatus comprising:

an elongated cavity formed in a metal mold for an injection molding;

a plurality of resin supplying ports arranged in a longitudinal direction of said cavity and provided for injecting a resin to the cavity;

an injection portion provided so as to freely move along a direction of arrangement of said resin supplying ports; and

an injection portion driving apparatus sequentially moving the injection portion to a position in correspondence to said resin supplying port.

15. (Withdrawn) An injection molding apparatus as claimed in claim 14, wherein one end and another end of said elongated cavity are positioned apart from each other in a vertical direction, and said injection portion moves between one end side and another end side of said cavity.

16. (Withdrawn) An injection molding apparatus as claimed in claim 14, wherein a detection sensor for detecting a charging amount of the molten resin is provided in a predetermined position of said cavity.

17. (Withdrawn) An injection molding apparatus as claimed in claim 14, further comprising a hot runner with a shutoff function for preventing the molten resin from flowing out.

18. (Withdrawn) An injection molding apparatus comprising:
an elongated cavity formed in a metal mold for an injection molding;
a plurality of resin supplying ports arranged in a longitudinal direction of said cavity and provided for injecting a resin to the cavity;
an injection portion provided so as to freely move along a direction of arrangement of said resin supplying ports; and
an injection portion driving apparatus sequentially moving the injection portion to a

position in correspondence to said resin supplying port,

wherein the molten resin is injected from each of the resin supplying ports while feeding a gas into the cavity so as to pressurize the cavity at a time of injecting the resin from each of the resin supplying ports, the gas pressurization is finished just before the resin is injected from the final resin supplying port, the resin is injected from the final resin supplying port, and the charging is finished.

19. (Withdrawn) An injection molding apparatus as claimed in claim 18, wherein said elongated cavity is formed so that one end and another end thereof are positioned apart from each other by a predetermined amount in a horizontal direction.

20. (Cancelled)